



DELL UltraSharp U3417W computer monitor 86.7 cm (34.1") 3440 x 1440 pixels UltraWide Quad HD LCD Black

Brand : DELL

Product family: UltraSharp

Product code: nelbo-U3417W

Product name : U3417W

- 86.72cm (34.14") Ultra-Wide Quad HD 3440 x 1440 Edge LED IPS

- 8ms, 21:9, 300cd/m², 1000:1

- USB, HDMI, DisplayPort, Mini DisplayPort

86.72cm (34.14") Ultra-Wide Quad HD 3440 x 1440 Edge LED IPS, 21:9, 300cd/m², 1.073B, 8ms, 178°/178°, 1000:1

DELL UltraSharp U3417W computer monitor 86.7 cm (34.1") 3440 x 1440 pixels UltraWide Quad HD LCD Black:

Immersive display. Immaculate performance.

Discover precision performance on a 34" curved monitor that elevates your work, gaming and entertainment.

- Immerse yourself in the curve: Increased screen curvature enhances your field of vision by delivering near-uniform focus, so you can immerse yourself in work or play.

- High performance perfected: WQHD 3440x1440 resolution offers stunning clarity while the flicker-free screen with ComfortView optimizes eye comfort.

- Multitasking made simple: Work from two PCs simultaneously on one screen. Arrange your screen using layout apps in Dell Easy Arrange and both picture-in-picture and picture-by-picture features.



Performance		Weight & dimensions	
NVIDIA G-SYNC *	✗	Depth (without stand)	58.4 mm
AMD FreeSync *	✗	Height (without stand)	363.7 mm
		Weight (without stand)	7.7 kg
Multimedia		Packaging data	
Number of speakers	2	Package width	253 mm
RMS rated power	18 W	Package depth	962.9 mm
Built-in speaker(s) *	✓	Package height	486.9 mm
Built-in camera *	✗	Package weight	15.4 kg
Design		Corrugated cardboard, Paper molded pulp, Polyethylene terephthalate (PET), Low-density polyethylene (LDPE)	
Market positioning *	Business		
Product colour *	Black	Package material	
Ports & interfaces		Packaging content	
USB version	3.2 Gen 1 (3.1 Gen 1)	Stand included	✓
Built-in USB hub *	✓	Cables included	AC, HDMI
USB hub version	3.2 Gen 1 (3.1 Gen 1)		
Number of upstream ports	2	Other features	
USB Type-A downstream ports quantity	4	On/off switch	✓
DVI port	✗	TV tuner integrated	✗
HDMI *	✓	Energy efficiency class (old)	A
HDMI ports quantity	2	Dell E-Value Code	U3417W
HDMI version	2.0	Supplied AC adapter type	LED
DisplayPorts quantity	2	Certification	RoHS, BFR/PVC Free
DisplayPort version	1.2	Recycling data	
Mini DisplayPorts quantity	1	Corrugated cardboard content per package	4.08 kg
Audio input	✗	Low-density polyethylene (LDPE) content per package	80 g
Headphone out *	✗	Paper molded pulp content per package	1.24 kg
AC (power) in	✓	Polyethylene terephthalate (PET) content per package	53 g
Ergonomics		Polypropylene (PP) content per package	0 g
VESA mounting *	✓	Polystyrene (PS) content per package	0 g
Panel mounting interface	100 x 100 mm	Thin Client	
Cable lock slot *	✓	Thin client installed	✗
Height adjustment *	✓		
Adjustable height (max)	11.5 cm		

Display

Display diagonal *	86.7 cm (34.1")
Display resolution *	3440 x 1440 pixels
HD type *	UltraWide Quad HD
Native aspect ratio *	21:9
Display technology *	LCD
Panel type *	IPS
Backlight type	Edge LED
Touchscreen *	✗
Display brightness (typical)	300 cd/m²
Response time *	8 ms
Display surface	Matt
Screen shape *	Curved
Supported graphics resolutions	3440 x 1440
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	5000000:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.073 billion colours
SmartResponse	5 ms
Pixel pitch	0.233 x 0.233 mm
Pixel density	109 ppi
Horizontal scan range	30 - 134 kHz
Vertical scan range	48 - 76 Hz
Viewable size, horizontal	80 cm
Viewable size, vertical	33.5 cm
Viewable size diagonal	86.7 cm
Colour gamut standard	sRGB
3D	✗

Ergonomics

Swivelling	✓
Swivel angle range	-30 - 30°
Tilt adjustment	✓
Tilt angle range	-5 - 21°

Power

Power consumption (typical) *	50 W
Power consumption (standby) *	0.5 W
Power consumption (max)	130 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	1.5 A
Energy efficiency scale	A++ to E
Annual energy consumption	63 kWh

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 80%
Storage relative humidity (H-H)	5 - 90%
Operating altitude	0 - 5000 m
Non-operating altitude	0 - 12191 m

Weight & dimensions

Width (with stand)	813.6 mm
Depth (with stand)	226.3 mm
Height (with stand)	531.9 mm
Weight (with stand)	10 kg
Width (without stand)	813.6 mm